

DATA SHEET

CODE: AWM70H60THEY

NAME: Everyday Direct Thermal Paper SA ECO

Description:

The face-stock is with ECO coated direct thermal (DT) paper.. This ECO Coated DT Paper with standard sensitivity,it is used for retail and logistics labeling in short life applications.

PROPERTY

PARAMETER	VALUE	
Face stock	Type/ Materials	Matte Paper with ECO coating
	Caliper ISO536/534	70 (gram/m ²) / 72 (um) ±5%
	Whiteness ISO 2470	≥85%
	Water-resistance	NA
	Oil-resistance	NA
	Plasticizer-resistance	NA
Adhesive	Type/ Materials	Hot melt
	Caliper (um)	18 ±2
	Initial Loop Tac (N/in) FTM-9 Glass	≥16
	90°Peel adhesion (N/in) FTM-2 St.	≥8
	Min. Applying Temp. (°C)	+5 °C
	Service Temp. (°C)	-20 to 65
Liner	Type/ Materials	Yellow glassine paper
	Caliper(um/gram) ISO536/534	53 / 58 ±4%
Regular size	Width /m	1.07, 1.53
	Length /m	3000, 6000
Storage	Under Temp. 23±2°C, humidity 50±5%	24 Months from the date of manufacture

PRINTING

Thermal Transfer	Direct Thermal	Flexography	Screen	Offset	Laser Toner	HP Indigo	Aqua Inkjet	UV Digital
	Y							

- Do not serve in where expose to sun light directly or where long time above 50 °C

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.